# WALLY A

### Accent Luminaire for Baldur System



#### **DESCRIPTION**

WALLY from Nordeon USA is a versatile lighting instrument well suited for wall washing, accenting, and general illumination in interior applications. The die-cast aluminum accent luminaire with yoke is horizontally and vertically adjustable on a single tray for easy installation into the Baldur trunking system. Available color temperatures are 3000K and 4000K.



Date:	Туре:	Catalog Number:
Project Name:		

#### ORDERING INFORMATION

MODEL	CCT/CRI	VOLT	OPTICS	LENGTH	FINISH
BDWA	930	UNV	WB	1.8FT	WH
Baldur Wally Accent	3000K at 90 CRI	120-277v	Wide Beam	1.8' nominal length	White
	840				BL
	4000K at 80 CRI				Black
					SI
					Silver





## Accent Luminaire for Baldur System



#### PRODUCT SPECIFICATIONS

HOUSING	Die Cast Aluminum Housing	
POWER CONSUMPTION	38 watts	
EFFICACY	Up to 120 lumens per watt	
LUMEN MAINTENANCE	L80/B10: 50,000 hours	
OPTICS	CoB LED with formed aluminum reflector and tempered glass lens	
OPERATING TEMPERATURE	-20°C to 30°C (-4°F to 86°F)	
DRIVERS	Electronic Driver, 120-277V, 50/60Hz. Less Than 20% THD and PF>0.90	
INGRESS PROTECTION	IP20	
CERTIFICATIONS	C S Us	
FINISH	White, Black, Silver	
WARRANTY	5-Year Warranty	






#### PHOTOMETRICS - WALLY ACCENT LUMINAIRE


Color Temperature	3000K	4000K	
CRI	90CRI	80CRI	
Delivered Lumens	4042 lumens	4574 lumens	
Maximum Candela	2977 cd	3369 cd	
Horizontal Beam Angle (50%)	87.7°	87.7°	
Vertical Beam Angle (50%)	60.6°	60.6°	

#### 3000K



Maximum Candela = 2976.867 Located At Horizontal Angle = 0, Vertical Angle = 0 H - Horizontal Axial Candela V - Vertical Axial Candela

#### 4000K



Maximum Candela = 3368.502 Located At Horizontal Angle = 0, Vertical Angle = 0 H - Horizontal Axial Candela V - Vertical Axial Candela



#### **DIMENSIONS**

